

# FASTANK® BUND- SECONDARY CONTAINMENT

• Fire Services • Industrial • Public Utilities • Contractors • Environmental

**A multi purpose secondary containment system to catch fuel or chemical spills. Meets Environmental Legislation - ISO 14000.**



## Applications

- Bunding for mobile plant & generators
- Catches fuel and chemical spills or drips
- Portable decontamination pool
- Bunding of oil tanks & drums
- Effluent, sewage & waste liquid catchment
- Protects the environment from accidental spills
- Temporary liquid storage / drip tray
- Vehicle & equipment washdown

## Features

- Drive-in by lowering end wall
- Small packaged weight & volume
- High level of chemical resistance; compatibility chart available
- Aluminium supports ensure upright walls
- Designed for internal or external use
- Smooth profile facilitates easy cleaning

## Benefits

- Helps your business comply with environmental & safety regulations
- Tool free assembly in minutes with no operator training
- Standard sizes available ex-stock. Also made to customer requirements
- Possible to re-site quickly
- Maintenance free - corrosion resistant materials
- Air inflation not required
- Sump area easily cleaned after use
- Cost effective solution for environmental protection

## Specifications

Assembled Size	Packaged Size	Packaged Weight	Capacity
1 x 1 x 0.25m h 40 x 40 x 10" h	0.6 x 0.10 x 0.30m h 24 x 4 x 12" h	5.2 kg 11.5 lbs	250 Litres 60 US Gal
1 x 2 x 0.25m h 40 x 78 x 10" h	0.6 x 0.10 x 0.30m h 24 x 4 x 12" h	7.5 kg 16.5 lbs	500 Litres 120 US Gal
2 x 2 x 0.25m h 78 x 78 x 10" h	0.6 x 0.15 x 0.35m h 24 x 6 x 14" h	11 kg 24.5 lbs	1000 Litres 240 US Gal
2 x 3.5 x 0.25m h 78 x 138 x 10" h	0.6 x 0.15 x 0.35m h 24 x 6 x 14" h	16 kg 35.5 lbs	1750 Litres 420 US Gal
2.5 x 6 x 0.25m h 98 x 236 x 10" h	0.8 x 0.15 x 0.6m h 32 x 6 x 24" h	25 kg 55.0 lbs	3750 Litres 900 US Gal
3.5 x 4.5 x 0.25m h 138 x 177 x 10" h	0.8 x 0.15 x 0.6m h 32 x 6 x 24" h	28 kg 61.5 lbs	4000 Litres 960 US Gal

## Accessories

- Polythene Liner** Extended chemical resistance & easy cleaning of unit.
- Overflow Control Kit** For emptying, decanting contents, level adjustment & overflow control.
- Ground Mat** Extra protection on rough ground.
- Protective Mat** Protection from sharp equipment inside tank.

FASTANK Bund is manufactured to ISO9001:2000 Quality Standard from 25oz (850gsm) rip stop acrylic & vinyl coated polyester fabric. Aluminium wall supports.

Registered Design No. 2104475



Abzorboil Pollution Control  
Robtec House, High Street, Cleobury Mortimer, Kidderminster, DY14 8DP  
Tel: +44 (0) 1299 270179; Fax: +44 (0) 1299 271015

Email: [sales@abzorboil.com](mailto:sales@abzorboil.com) Web: <http://www.abzorboil.com>

Specifications may vary due to our policy of constant improvement. © Fast Engineering Ltd, 2005

FASTANK is  
made to ISO9001:2000  
Quality Standard

# FASTANK® BUND- SECONDARY CONTAINMENT

## Accessories

**Polythene Liner:** This protects the inside of the tank from aggressive liquids. It minimises the cleaning of FASTANK after use with dirty or oily contents. Prevents cross contamination when storing different liquids. Made from 125micron (500 gauge) virgin food grade polythene. This is a cost effective accessory.



**Overflow Control Kit:** Automatically drains rainwater from underneath floating oil or debris. Offers controlled overflow and emptying of bund. Valve outlet for flow regulation, corrosion resistant and trouble free.

**Ground Mat:** Provides extra protection on rough or sharp ground. Made from heavy duty vinyl coated reinforced fabric.



**Protective Mat:** Provides extra protection for inside of tank from sharp equipment or wheel loads .

**Fast Engineering Ltd. can also manufacture to your special requirements**



Abzorboil Pollution Control  
Robtec House, High Street, Cleobury Mortimer, Kidderminster, DY14 8DP  
Tel: +44 (0) 1299 270179; Fax: +44 (0) 1299 271015  
Email: [sales@abzorboil.com](mailto:sales@abzorboil.com) Web: <http://www.abzorboil.com>  
Specifications may vary due to our policy of constant improvement. © Fast Engineering Ltd, 2005

FASTANK is  
made to ISO9001:2000  
Quality Standard